



CASSETTES TKC FREYVEN



LINEA

MODO

INCLUYE REJILLA MODELO MBQ8-C

VOLTAJE

FASES

PROS

ON / OFF

FRIO / CALOR

220V

MONOFASICO

OPERACIÓN

SILENCIOSA

TOTALINE®

Freyven



CASSETTES TKC FREYVEN

EVAPORADORES	SISTEMA EVAP REJILLA	EVAP SF 24KBTU	EVAP SF 36KBTU	EVAP SF 48KBTU	EVAP SF 60KBTU
		50TKC243A	50TKC363A	50TKC483A	50TKC603A
		40TKC243A	40TKC363A	40TKC483A	40TKC603A
		MBQ8-C	MBQ8-C	MBQ8-C	MBQ8-C
CAPACIDAD	TON	2	3	4	5
	BTU	24,000	36,000	48,000	60,000
VOLTAJE-FASES		230V / 1 Fase	230V / 1 Fase	230V / 1 Fase	230V / 1 Fase
CONSUMOS	W	2,670	4,138	5,347	6,153
	A	12	17.6	22.8	26.3
VOLUMEN DE AIRE BAJA	CFM	530	589	589	589
VOLUMEN DE AIRE MEDIA		618	765	765	765
VOLUMEN DE AIRE ALTA		706	942	942	942
MOTORES	QTY	1	3	3	3
	W	150	160	160	160
	A	0.7	0.8	0.8	0.8
NIVEL DE RUIDO BAJA	dB	40	42	42	42
NIVEL DE RUIDO MEDIA		43	44	44	44
NIVEL DE RUIDO ALTA		45	47	47	47
φ LIQUIDO	in	3/8	3/8	3/8	3/8
φ GAS		5/8	3/4	3/4	3/4
LARGO	cm	2.5	4.5	4.5	4.5
ALTO		67	95	95	95
ANCHO		105	95	95	95
PESO (NETO)	Kg	6	6	6	6
TUBERIA COND		OD25	OD32	OD32	OD32
OBSERVACIONES	CONEXIÓN CONDESADORA ASIATICA R-R Y C-C / CONEXIÓN CONDESADORA AMERICANA R-C Y C-R				

