



FREYVEN 53FV-D



REFRIGERANTE R-32

EQUIPO SILENCIOSO

TIMER

MODO SLEEP

MODO TURBO

MODO I FEEL

CUMPLE CON LA NOM-023

CUMPLE CON LA NOM-003

TOTALINE®

Freyven





FREYVEN 53FV-D

FREYVEN 53FV-D		SISTEMA EVAP COND	53FVC121D	53FVC123D	53FVC183D	53FVC243D	53FVC363D	53FVQ121D	53FVQ123D	53FVQ183D	53FVQ243D	53FVQ363D
			40FVC121D-E	40FVC123D-E	40FVC183D-E	40FVC243D-E	40FVC363D-E	40FVQ121D-E	40FVQ123D-E	40FVQ183D-E	40FVQ243D-E	40FVQ363D-E
			38FVC121D-C	38FVC123D-C	38FVC183D-C	38FVC243D-C	38FVC363D-C	38FVQ121D-C	38FVQ123D-C	38FVQ183D-C	38FVQ243D-C	38FVQ363D-C
			ON/OFF	ON/OFF	ON/OFF	ON/OFF	ON/OFF	ON/OFF	ON/OFF	ON/OFF	ON/OFF	ON/OFF
			SOLO FRIO	SOLO FRIO	SOLO FRIO	SOLO FRIO	SOLO FRIO	FRIO / CALOR	FRIO / CALOR	FRIO / CALOR	FRIO / CALOR	FRIO / CALOR
INFO. BÁSICA	CAPACIDAD	TON	1	1	1.5	2	3	1	1	1.5	2	3
		BTU	12,000	12,000	18,000	24,000	36,000	12,000	12,000	18,000	24,000	36,000
	VOLTAJE	V	115 V	230 V	230 V	230 V	230 V	115 V	230 V	230 V	230 V	230 V
	FASES	Φ	1F	1F	1F	1F	1F	1F	1F	1F	1F	1F
	FRECUENCIA	HZ	60 Hz	60 Hz	60 Hz	60 Hz	60 Hz	60 Hz	60 Hz	60 Hz	60 Hz	60 Hz
CONSUMO	ENFRIAMIENTO	W	1,140 W	1,280 W	1,840 W	2,360 W	3,470 W	1,140 W	1,280 W	1,840 W	2,360 W	3,470 W
	CALEFACCIÓN	A	N.A.	N.A.	N.A.	N.A.	N.A.	1,050 W	1,310 W	1,930 W	2,080 W	3,540 W
	ENFRIAMIENTO	A	9.90 A	6.10 A	8.90 A	11.10 A	16.40 A	9.90 A	6.10 A	8.90 A	11.10 A	16.40 A
	CALEFACCIÓN	A	N.A.	N.A.	N.A.	N.A.	N.A.	9.10 A	6.30 A	9.30 A	10.00 A	16.90 A
VOLUMEN DE AIRE	VOLUMEN DE AIRE	CFM	236	236	412	530		236	236	412	530	
			312	312	471	589	825	312	312	471	589	825
			353	353	530	677		353	353	530	677	
	RPM		1050	1050	1130	1100	900	1050	1050	1130	1100	900
	NIVEL DE RUIDO		1,150	1,150	1,260	1,250	1,100	1,150	1,150	1,260	1,250	1,100
			1,250	1,250	1,360	1,400	1,270	1,250	1,250	1,360	1,400	1,270
			33	33	37	40	42	33	33	37	40	42
		dB	36	36	42	43	45	36	36	42	43	45
DATOS TÉCNICOS	REFRIGERANTE	TIPO	R32	R32	R32	R32	R32	R32	R32	R32	R32	R32
	CARGA DE REF	g	350g	430g	600g	800g	1200g	460g	470g	660g	900g	1450g
	COMPRESOR	TIPO	ROTATIVO	ROTATIVO	ROTATIVO	ROTATIVO	ROTATIVO	ROTATIVO	ROTATIVO	ROTATIVO	ROTATIVO	ROTATIVO
	LRA	A	50	24	46	46	80	50	24	46	46	80
	POTENCIA	W	1,115	930	1,450	1,865	3,085	1,115	930	1,450	1,865	3,085
	DESHUMIDIFICACIÓN	LITROS/HORA	1.3	1.3	2.0	2.2	3.2	1.3	1.3	2.0	2.2	3.2
	EFICIENCIA	PINTA/DÍA	66	66	101	112	162	66	66	101	112	162
	SEER		12	12	12	12	12	12	12	12	12	12
EVAP	PRESIÓN DESCARGA	MPa	4.3	4.3	4.3	4.3	4.3	4.3	4.3	4.3	4.3	4.3
	PRESIÓN SUCCIÓN		1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2
	Φ GAS	in	1/2"	1/2"	1/2"	1/2"	5/8"	1/2"	1/2"	1/2"	1/2"	5/8"
	Φ LÍQUIDO		1/4"	1/4"	1/4"	1/4"	1/4"	1/4"	1/4"	1/4"	1/4"	1/4"
COND	LARGO	cm	78	78	91	101	119	78	78	91	101	119
	ANCHO		25	25	29	32	34	25	25	29	32	34
	ALTO		20	20	21	22	26	20	20	21	22	26
	PESO	Kg	8.5	8.5	10	11.5	16	8.5	8.5	10	11.5	16
	LARGO	cm	79	79	86	86	98	79	79	86	86	98
	ANCHO		29	29	35	35	42	29	29	35	35	42
	ALTO		50	50	60	60	80	50	50	60	60	80
	PESO	Kg	23	23	31	35	51.5	24	24	34	38	55



TOTALINE®