



FREYVEN 53FY-D



REFRIGERANTE R-32
EQUIPO SILENCIOSO
TIMER
MODO SLEEP
MODO TURBO
MODO I FEEL

CUMPLE CON LA NOM-003
CUMPLE CON LA NOM-017
CONECTIVIDAD WIFI

TOTALINE®

Freyven





FREYVEN 53FY-D

FREYVEN 53FY-D		SISTEMA EVAP COND	53FYC121D 40FYC121D-E 38FYC121D-C	53FYC123D 40FYC123D-E 38FYC123D-C	53FYC183D 40FYC183D-E 38FYC183D-C	53FYC243D 40FYC243D-E 38FYC243D-C	53FYC363D 40FYC363D-E 38FYC363D-C	53FYQ121D 40FYQ121D-E 38FYQ121D-C	53FYQ123D 40FYQ123D-E 38FYQ123D-C	53FYQ183D 40FYQ183D-E 38FYQ183D-C	53FYQ243D 40FYQ243D-E 38FYQ243D-C	53FYQ363D 40FYQ363D-E 38FYQ363D-C
			INVERTER SOLO FRIO	INVERTER SOLO FRIO	INVERTER SOLO FRIO	INVERTER SOLO FRIO	INVERTER SOLO FRIO	INVERTER FRIO / CALOR	INVERTER FRIO / CALOR	INVERTER FRIO / CALOR	INVERTER FRIO / CALOR	INVERTER FRIO / CALOR
CONSUMO INFO. BÁSICA	CAPACIDAD	TON BTU	1 12.000	1 12.000	1,5 18.000	2 24.000	3 36.000	1 12.000	1 12.000	1,5 18.000	2 24.000	3 36.000
	VOLTAJE	V	115 V	230 V	230 V	230 V	230 V	115 V	230 V	230 V	230 V	230 V
	FASES	φ	1F	1F	1F	1F	1 F	1F	1F	1F	1F	1F
CONFORTE	FRECUENCIA	Hz	60 Hz	60 Hz	60 Hz	60 Hz	60 Hz	60 Hz	60 Hz	60 Hz	60 Hz	60 Hz
	ENFRIAMIENTO	W	1.154	1.260	1.714	2.350	2.542	1.236	1.260	1.820	2.365	3.517
	CALEFACCIÓN	N/A	N/A	N/A	N/A	N/A	N/A	1.000	1.100	1.480	2.010	3.197
DATOS TÉCNICOS	ENFRIAMIENTO	A	13	10	12	12	16	13	8	12	12	19
	CALEFACCIÓN	N/A	N/A	N/A	N/A	N/A	N/A	14	7	12	13	19
	VOLUMEN DE AIRE	CFM RPM	300 1350	300 1270	600 1350	800 1270	850 1250	300 1350	300 1250	600 1400	800 1270	900 1250
EVAP	NIVEL DE RUIDO	dB	40 36 33	40 37 33	46 41 35	49 46 41	49 46 41	40 36 33	40 37 33	45 39 34	47 45 39	49 44 38
	REFRIGERANTE	TIPO	R32	R32	R32	R32	R32	R32	R32	R32	R32	R32
	CARGA DE REF	gr	400	370	640	800	940	500	475	670	1040	1590
COND	COMPRESOR	TIPO	ROTATIVO	ROTATIVO	ROTATIVO	ROTATIVO	ROTATIVO	ROTATIVO	ROTATIVO	ROTATIVO	ROTATIVO	ROTATIVO
	LRA	A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
	POTENCIA	W	778	845	970	1085	1100	778	845	970	1.085	2.065
COND	DESHUMIDIFICACIÓN	LITROS/HORA PINTA/DÍA	1,3 2,7	1,3 2,7	1,8 3,8	2,4 5,1	2,4 5,1	1,3 2,7	1,3 2,7	1,8 3,8	2,4 5,1	3,6 7,6
	EFICIENCIA	SEER	16	16	16	16	16	17	16	18	18	20
	PRESIÓN DESCARGA	MPa	4,5	4,5	4,5	4,5	4,5	4,5	4,5	4,5	4,5	4,5
COND	PRESIÓN SUCCIÓN		1,9	1,9	1,9	2	2	1,9	1,9	1,9	1,9	1,9
	φ GAS	in	3/8"	3/8"	1/2"	1/2"	5/8"	3/8"	3/8"	3/8"	1/2"	5/8"
	φ LÍQUIDO		1/4"	1/4"	1/4"	1/4"	1/4"	1/4"	1/4"	1/4"	1/4"	1/4"
COND	LARGO	cm	25	25	29	32	36	25	25	29	32	36
	ALTO	cm	78	78	91	101	119	78	78	91	101	119
	ANCHO	cm	20	20	21	22	26	20	20	21	22	26
COND	PESO	Kg	8	8	9,5	12	17	8	8	9	12	17
	LARGO	cm	29	28	31	35	42	29	28	31	35	42
	ALTO	cm	78	72	81	86	98	78	72	81	86	98
COND	ANCHO	cm	50	46	55	60	80	50	46	55	60	80
	PESO	Kg	21	18	24,5	29	48	22	20	25	31	48



TOTALINE®